

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 949 506 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
13.10.1999 Bulletin 1999/41

(51) Int. Cl.⁶: **G01N 33/487**, G01N 33/48,
G01N 33/49

(21) Application number: **99105894.2**

(22) Date of filing: **24.03.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **06.04.1998 US 55385**

(71) Applicant: **Bayer Corporation**
Pittsburgh, PA 15205 (US)

(72) Inventor: **Perry, Joseph, E.**
Osceola, IN 46561 (US)

(74) Representative: **Burkert, Frank**
Bayer AG,
Konzernbereich RP
Patente und Lizenzen
51368 Leverkusen (DE)

(54) **Method and apparatus for data management authentication in a clinical analyzer**

(57) A method and apparatus are provided for data management authentication in a clinical analyzer. The clinical analyzer includes a sensor for receiving a user sample to be measured and a processor for performing a predefined test sequence for measuring a predefined parameter value. A memory is coupled to the processor for storing predefined parameter data values. An authentication password is associated with each data transmission by the clinical analyzer and read by an associated computer system to validate each data transmission. The authentication password is generated by the clinical analyzer utilizing predetermined information in each data transfer.




FIG. 1

EP 0 949 506 A2

Description

Field of the Invention

[0001] The present invention generally relates to a clinical analyzer, and, more particularly, to a new and improved method and apparatus for data management authentication in a clinical analyzer.

Description of the Prior Art

[0002] The quantitative determination of analytes in body fluids is of great importance in the diagnoses and maintenance of certain physiological abnormalities. For example lactate, cholesterol and bilirubin should be monitored in certain individuals. In particular, the determination of glucose in body fluids is of great importance to diabetic individuals who must frequently check the level of glucose in their body fluids as a means of regulating the glucose intake in their diets. While the remainder of the disclosure herein will be directed towards the determination of glucose, it is to be understood that the procedure and apparatus of this invention can be used with other diagnostic systems.

[0003] Diagnostic systems, such as, blood glucose systems include a biosensor used to calculate the actual glucose value based on a measured output (either current or color) and the known reactivity of the reagent sensing element used to perform the test. The test results typically are displayed to the user and stored in a memory in the blood glucose monitor. It is desirable to periodically transfer the multiple stored values from the blood glucose monitor to a separate computer, for example to enable analysis by a doctor for the blood glucose monitor user.

[0004] One known communications protocol for such data transfer is the ASTM Standard E1381-91, "Specification for Low-Level Protocol to Transfer Messages Between Clinical Laboratory Meters and Computer Systems" and ASTM Standard E1394-91, "Standard Specifications for Transferring Information Between Clinical Meters and Computer Systems". ASTM Standard E1381-91 defines the low-level data transfer protocol and ASTM Standard E1394-91 defines the data format.

[0005] Multiple commercially available clinical analyzer are available for patient use. Due to differences between various commercially available clinical analyzer, a need exists for a method and apparatus for data management authentication in a clinical analyzer to validate data transmissions and to identify a particular type of clinical analyzer. Otherwise if a patient changes to a different type of clinical analyzer, then analysis by the patient's doctor of the data transfers from the different clinical analyzer likely would provide erroneous results.

Summary of the Invention

[0006] Important objects of the present invention are

to provide a new and improved method and apparatus for data management authentication in a clinical analyzer; to provide such method and apparatus that eliminates or minimizes the need for user interaction; and to provide such method and apparatus that overcome some disadvantages of prior art arrangements.

[0007] In brief, a method and apparatus are provided for data management authentication in a clinical analyzer. The clinical analyzer includes a sensor for receiving a user sample to be measured and a processor for performing a predefined test sequence for measuring a predefined parameter value. A memory is coupled to the processor for storing predefined parameter data values. An authentication password is associated with each data transmission by the clinical analyzer to an associated computer system. The authentication password is read by the associated computer system to validate each data transmission. The authentication password is generated by the clinical analyzer utilizing predetermined information in each data transmission.

Brief Description of the Drawings

[0008] The present invention together with the above and other objects and advantages may best be understood from the following detailed description of the preferred embodiments of the invention illustrated in the drawings, wherein:

FIG. 1 is an enlarged perspective view of a clinical analyzer shown in an open position in accordance with the present invention;

FIG. 2 is an enlarged perspective view of the clinical analyzer of FIG. 1 shown in a closed position;

FIG. 3 is a block diagram representation of clinical analyzer circuitry in accordance with the present invention of the clinical analyzer of FIG. 1;

FIG. 4 is a flow chart illustrating exemplary sequential steps of a data management authentication method in accordance with the present invention of the clinical analyzer of FIG. 1; and

FIG. 5 is a chart illustrating an exemplary message format including an authentication password in accordance with the present invention of the clinical analyzer of FIG. 1.

Detailed Description of the Preferred Embodiments

[0009] Having reference now to the drawings, in FIGS. 1 and 2 there is illustrated a clinical analyzer designated as a whole by the reference character 10 and arranged in accordance with principles of the present invention. Clinical analyzer 10 includes a clam-shell type enclosure 12 formed by a base member 14 and a cover mem-

ber 16. Base and cover members 14 and 16 are pivotably attached together at a first end 18 and are secured together by a latch member 20 at a second, opposite end 22. A display 24, such as a liquid crystal display (LCD) is carried by the cover member 16. To turn the clinical analyzer 10 on and off, a manually movable slide 28 mounted on the cover member 16 is moved between an open position shown in FIG. 1 and a closed position shown in FIG. 2.

[0010] In the closed or OFF position of FIG. 2, the slide 28 covers the display 24. A thumb grip 30 carried by the slide 28 is arranged for manual engagement by a user of the clinical analyzer 10 to select the ON and OFF positions. The thumb grip 30 also is movable from left to right in the OFF position of slide 28 for selecting a system test operational mode. When a user moves the slide 28 to the ON position of FIG. 1, the display is uncovered and a sensor 32 is presented. The sensor 32 extends through a slot 34 and is positioned outside the enclosure 12 for the user to apply a blood drop. A right button 42 and a left button or switch 44 (or switches A and B) are carried by the enclosure 12 for operation by a user to select predefined operational modes for the clinical analyzer 10, and for example, to set, recall and delete blood glucose readings and to set date, time, and options.

[0011] Referring also to FIG. 3, there is shown a block diagram representation of clinical analyzer circuitry designated as a whole by the reference character 50 and arranged in accordance with principles of the present invention. Clinical analyzer circuitry 50 includes a microprocessor 52 together with an associated memory 54 for storing program and user data. The display 24 is operatively controlled by the microprocessor 52. A meter function 56 coupled to the sensor 32 is operatively controlled by the microprocessor 52 for recording blood glucose test values. A battery monitor function 58 is coupled to the microprocessor 52 for detecting a dead battery (not shown) condition. An alarm function 60 is coupled to the microprocessor 52 for detecting predefined system conditions and for generating alarm indications for the user of clinical analyzer 10. A data port or communications adapter 62 couples data to and from a connected computer system 64 via a communications link 66. An ON/OFF input at a line 28A responsive to the user ON/OFF operation of the slide 28 is coupled to the microprocessor 52 for performing the blood test sequence mode of clinical analyzer 10. Microprocessor 52 contains suitable programming to perform the methods of the invention as illustrated in FIGS. 4 and 5.

[0012] In accordance with the invention, an authentication password generally designated by 504 in FIG. 5 is associated with each data transmission or message generally designated by 500 by the clinical analyzer 10. The authentication password 504 is read by the associated computer system 64 to validate each data transmission. The authentication password 504 is generated by the clinical analyzer 10 utilizing predetermined infor-

mation in each data transmission.

[0013] Referring to FIG. 4, there are shown exemplary steps for password computation of the invention starting at a block 400. First a fourteen day average glucose is computed and stored as AVG as indicated at a block 402. A number of minutes since midnight (hrs * sixty + mins), is computed and stored as MINS as indicated at a block 404. A number of days since an predetermined date, such as December 31, 1989, to the present date is computed, (full years * three hundred sixty five + leap years * one + number of days elapsed in current year), and stored as DAYS as indicated at a block 406. An eight bit random number is generated and stored as RND as indicated at a block 408. Then the password is computed, $\text{passwd} = \text{RND} * \text{two hundred fifty six} + ((\text{AVG} + \text{MINS} + \text{DAYS}) \text{MODULO two hundred fifty six})$ as indicated at a block 410. This completes the sequential steps as indicated at a block 412.

[0014] FIG. 5 illustrates an exemplary message format generally designated by 500 of the invention used for each data transfer from the clinical analyzer 10 to the associated computer system 64. Each data transfer or message 500 includes a message header 502 including a predefined field containing the authentication password 504. Another predefined field in the message header 502 contains a current date stamp 506 for the message 500. Each data transfer or message 500 includes a plurality of data records 508. In FIG. 5, five example data records 508 are shown and labeled R1, R2, R3, R4 and R5. An authentication password 504 of -18572 is shown with a date stamp 506 of June 16, 1997, time 1307 or 1:07PM. The fourteen day average glucose is shown as 189 in record R1 including the universal test ID is "^^^GlucoseA".

[0015] The ASTM E1394-91 standard defines a header record that advantageously is used for the message header 502. The authentication password 504 is contained in one field within the header record defined as an "access password" field by the ASTM E1394-91 standard. The clinical analyzer 10 transmits the authentication password 504 as a signed integer, a 16 bit value. The signed integer is actually transmitted as a sequence of ASCII (American National Standard for Information Interchange) characters which represent the integer. The range for the authentication password 504 is from "-32767" to "32768".

[0016] The eight most significant bits of the authentication password 504 is an 8-bit random number, that must change randomly from transmission to transmission of messages 500. The eight least significant bits of the authentication password 504 is based on the date and time of the message contained in time stamp field 506 of the header record 502 and the 14 day average glucose contained in a result record 508 when the universal test ID is "^^^GlucoseA", as shown in data record R1 in FIG. 5. The computed part of the password is calculated by adding the number of minutes since midnight to the number of days since December 31,

1989, plus the 14 day average glucose (in mg/dL). Only the 8 least significant bits of the computation are kept. If the clinical analyzer 10 provides glucose values in mmol/L, then the 14 day average value is first converted to mg/dL (multiply by 18 and rounded to an integer) before being added in the password calculation.

[0017] The 8-bit random part (most significant byte) is concatenated to the 8-bit computed part (least significant byte) which results in a 16 bit value for the authentication password 504. The authentication password 504 is interpreted as a 16 bit signed integer ranging in value from -32767 to 32768. It is transmitted as the sequence of ASCII characters which represent the integer.

[0018] When computer system 64 receives the transmission from a particular clinical analyzer 10, it converts the ASCII characters in the password field to an integer. The 8 most significant bits are ignored, the 8 least significant bits are verified against the calculation of the authentication password 504 as detailed above. For example, the authentication password 504 of -18572 is compared with a computed value by the computer system 64. The computer system 64 uses the same equation, shown in block 410 in FIG. 4 for computing the authentication password 504, as used by the clinical analyzer 10. The DAYS value of the number of days since December 31, 1989 until the date stamp date of June 16, 1997 is calculated by (7 full years * three hundred sixty five + 2 leap years * one day/leap-year + number of days elapsed in current year (31 + 28 + 31 + 30 + 31 + 16) which equals 2724. The time calculation (minutes since midnight) equals ((13 hours * 60 minutes/hour) + 7 minutes) which equals 787. The computation is verified as follows (2724 + 787 + 189) which equals 3700 or 0E74 total in hexadecimal, keeping the least significant 8-bits in hexadecimal or 74 in hexadecimal which equals 116 decimal. The access password is -18572 in decimal or B774 in hexadecimal. Keeping the least significant bits of the result leave 74 in hexadecimal which equals 116 decimal. Thus, the authentication password 504 agrees with the computed value for the example data transfer message 500 of FIG. 5. Only when the authentication password 504 agrees with the computed value is the clinical analyzer 10 identified as a valid meter.

[0019] While the present invention has been described with reference to the details of the embodiments of the invention shown in the drawings, these details are not intended to limit the scope of the invention as claimed in the appended claims.

Claims

1. A clinical analyzer comprising:

sensor means for receiving a user sample;
processor means responsive to said user sample receiving means for performing a prede-

fined test sequence for measuring a predefined parameter value;
memory means coupled to said processor means for storing said predefined parameter data values;
communications means coupled to said processor means for transferring data to a computer system; each said data transfer including an authentication password and said predefined parameter data values; said authentication password used by said computer system to validate each said data transfer.

2. A clinical analyzer as recited in claim 1 wherein said authentication password is generated by said processor means utilizing predetermined information in each data transfer.
3. A clinical analyzer as recited in claim 2 wherein said predetermined information in each data transfer includes a time stamp value.
4. A clinical analyzer as recited in claim 3 wherein said time stamp value includes a current date and time value for said data transfer.
5. A clinical analyzer as recited in claim 4 wherein said predetermined information in each data transfer includes a fourteen day average glucose value.
6. A clinical analyzer as recited in claim 1 wherein each said data transfer includes said authentication password in a message header and said predefined parameter data values are included in a plurality of results records, said results records following said message header.
7. A clinical analyzer as recited in claim 6 wherein said message header includes a current time stamp value for said data transfer.
8. A clinical analyzer as recited in claim 7 wherein one of said plurality of results records includes a fourteen day average glucose value.
9. A clinical analyzer as recited in claim 8 wherein said authentication password generated by said processor means is read and compared with a calculated value by said computer system utilizing said current time stamp value and said fourteen day average glucose value.
10. A method for validating each data transfer from a clinical analyzer to a computer system comprising the steps of:

providing the clinical analyzer with a sensor for receiving a user sample and a processor for

performing a predefined test sequence for
measuring a predefined parameter value;
storing said predefined parameter values, and
transferring stored data to a computer system;
each said data transfer including the step of
calculating an authentication password, and
transferring said authentication password and
said predefined parameter data values; said
authentication password used by said compu-
ter system to validate each said data transfer.

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3

FIG. 4





FIG. 5



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 949 506 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
26.06.2002 Bulletin 2002/26

(51) Int Cl.7: **G01N 33/487, G06F 1/00,
A61B 5/00**

(43) Date of publication A2:
13.10.1999 Bulletin 1999/41

(21) Application number: **99105894.2**

(22) Date of filing: **24.03.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Perry, Joseph, E.**
Osceola, IN 46561 (US)

(74) Representative: **Burkert, Frank**
Bayer AG,
Konzernbereich RP
Patente und Lizenzen
51368 Leverkusen (DE)

(30) Priority: **06.04.1998 US 55385**

(71) Applicant: **Bayer Corporation**
Pittsburgh, PA 15205 (US)

(54) **Method and apparatus for data management authentication in a clinical analyzer**

(57) A method and apparatus are provided for data management authentication in a clinical analyzer. The clinical analyzer includes a sensor for receiving a user sample to be measured and a processor for performing a predefined test sequence for measuring a predefined parameter value. A memory is coupled to the processor

for storing predefined parameter data values. An authentication password is associated with each data transmission by the clinical analyzer and read by an associated computer system to validate each data transmission. The authentication password is generated by the clinical analyzer utilizing predetermined information in each data transfer.




FIG. 1

EP 0 949 506 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 10 5894

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	ALPERT N L: "I-STAT POINT-OF-CARE TESTING SYSTEM" CLINICAL INSTRUMENT SYSTEMS, MCNAMARA PUB., NEW YORK, NY., US, vol. 13, no. 4, 1994, pages 1-7, XP002139627 ISSN: 0730-7578	1,3-10	G01N33/487 G06F1/00 A61B5/00
Y	* page 2 - page 3 * ---	2	
Y	US 4 281 215 A (ATALLA MARTIN M) 28 July 1981 (1981-07-28) * abstract; figures 1A,1B * ---	2	
A	MANBER U: "A simple scheme to make passwords based on one-way functions much harder to crack" COMPUTERS & SECURITY. INTERNATIONAL JOURNAL DEVOTED TO THE STUDY OF TECHNICAL AND FINANCIAL ASPECTS OF COMPUTER SECURITY, ELSEVIER SCIENCE PUBLISHERS. AMSTERDAM, NL, vol. 15, no. 2, 1996, pages 171-176, XP004008180 ISSN: 0167-4048 * page 173; figure 1 * ---	2	TECHNICAL FIELDS SEARCHED (Int.Cl.6) G01N A61B G06F
A	US 5 717 756 A (COLEMAN DAVID ALLEN) 10 February 1998 (1998-02-10) * column 2, line 7 * * column 3, line 31 - column 3, line 63; figures 5A,5B * ---	2,3	
A	EP 0 764 469 A (BAYER AG) 26 March 1997 (1997-03-26) * column 5, line 48 - column 5, line 52; figures 9A,9B * -----	5,8	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 2 May 2002	Examiner Wilhelm, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1603 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 10 5894

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

02-05-2002

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4281215	A	28-07-1981	CA 1149484 A1	05-07-1983
			CA 1159124 A2	20-12-1983
			CA 1159920 A2	03-01-1984
			CH 646558 A5	30-11-1984
			DE 2916454 A1	15-11-1979
			FR 2425114 A1	30-11-1979
			GB 2020513 A ,B	14-11-1979
			GB 2047506 A ,B	26-11-1980
			GB 2099195 A ,B	01-12-1982
			JP 54148402 A	20-11-1979
			JP 62283742 A	09-12-1987
			US 4268715 A	19-05-1981
US 5717756	A	10-02-1998	DE 69613648 D1	09-08-2001
			DE 69613648 T2	18-04-2002
			EP 0768595 A1	16-04-1997
			JP 9128337 A	16-05-1997
EP 0764469	A	26-03-1997	US 5665215 A	09-09-1997
			AU 703987 B2	01-04-1999
			AU 6580496 A	27-03-1997
			CA 2184315 A1	26-03-1997
			EP 0764469 A2	26-03-1997
			JP 9127038 A	16-05-1997